

2308 MULTI-SPINDLE ROTARY CUTTER



The 2308 models are designed to cut grass, weeds and up to 1 1/2" diameter brush. The lift and semi-mount models are equipped with twin beam axles and 15" laminated tires. The pull model has the heavy duty cushioned axles with larger 20" laminated tires. An optional hydraulic cylinder on the heavy duty axle allows for on-the-go cutting height adjustment. Rubber disc cross shafts between gearboxes absorb shock loads while keeping the blades timed with a 5 inch overlap to prevent streaking. Deep sidebands result in more volume area beneath the deck for cutting extra heavy growth conditions. The 2308 delivers performance you expect from Bush Hog® which includes rugged durability and a clean cut. Bush Hog®—Performance You Can Count On.

Bush Hog[®] 2308 Multi-Spindle Rotary Cutter





Cross Shaft From Splitter Box To Outboard Gear Box





	SPECIFICATIONS
MODEL	2308
Cutting Width	8-feet 3-inches
Transport Width	8-feet 10-inches
Length (Lift / Pull)	8-feet 9-inches / 12-feet 9-inches
Cutting Height	2 to 13-inches
Cutting Capacity	1 1/2-inches diameter
Hitch	Category 1 and 2 Standard and Quick Hitch. Pull is self leveling with dual leveling rods.
Deck Thickness	10-Gauge Steel
Side Bands	7-Gauge x 12-inches
Gearbox	(1 ea.) 140 HP* Center and (2 ea.) 75 HP* Outboards (540 RPM)
Driveshaft	ASAE Category 4 with slip clutch
Driveline Protection	2-Plate Slip Clutch
Blade Holder	Oval
Blades	1/2-inch x 4-inch Uplift
Blade Overlap	5-inches
Blade Tip Speed	16,173 FPM (540 RPM)
Wheels	Laminated Tire
Minimum Tractor HP	50 (Lift) / 40 (Pull)
Safety Deflectors	See enclosure selection
Safety Tow Chain	Standard (Pull type)
Warranty	Five Year Limited Gearbox Warranty

 $[\]hbox{*Gearbox rating based on field performance.}\\$

Dealer Info:

