



8900 Digger

100% American Made

Utilizes an Eaton® high torque hydraulic motor paired with an Auburn® planetary gearbox and Timken® tapered roller bearings

- 8900-4 - 10-20 GPM at 1500-3000 PSI
- 8900-7 - 14-30 GPM at 1500-3000 PSI
- 8900-8 - 14-30 GPM at 1500-3000 PSI

8900-4 & -7 have 2-9/16" rd. output spindle
8900-8 has 2" hex output spindle

Reversible hydraulic motor reduces stuck augers and broken shear bolts

Compatible with Danuser 2-9/16" rd. & 2" hex augers with 1/2" bolt holes

36" max. dia. auger

Mounts include Skid-Steer Quick Attach or Front-End Loader (Bolt-On Bucket & Quick Attach)

5-year warranty on gearbox



Edges & Teeth

Plain




- Sharp edge design
- Normal digging conditions

Serrated



- Serrated edge design
- Tear through compacted soils and light tree roots

Hole Digger Head



- Most aggressive design
- Steel cast head rips through clay, caliche, shale, mixed limestone, frozen ground, and light rock



Made in the U.S.A.

Visit our website to see more information on the 8900 Digger.

danuser.com



8900 Digger

Visit danuser.com for more Danuser attachments.



500 E. 3rd Street
P.O. Box 368
Fulton, MO 65251

573.642.2246 tel
573.642.2240 fax
sales@danuser.com

danuser.com



Established in 1910, DANUSER has been family owned and operated by four generations. We have manufactured auger systems since the mid-1940's. With over 70 years of design and manufacturing experience, our machines have dug millions of holes. Today our commitment to our customer remains to design and build products that are the benchmark of quality, reliability, and longevity. In the words of our founder K.B. Danuser, "Good enough won't do - it must be right."

DANUSER manufactures several attachments for various equipment, serving several industries worldwide. Please visit www.danuser.com to see our full line of attachments.

Danuser reserves the right to make changes in design, specifications, and prices without notice and without incurring any obligation relating to such changes.