

DISC PLOW



ADB1 SERIES


GETS MORE FOR YOUR FIELD





BISON

DISC PLOW ADB1 SERIES



The proper functioning of the disc plow is achieved by combining two or more simple adjustments.

It has two angles of attack for more or less aggressiveness of the implement.



A very versatile disc plow, as it adapts to different conditions and types of existing agricultural soil for a uniform fallow at the required depth.

Steel frame without any cast-iron parts making it stronger and heavier to prevent breaking the disc-holder.



Guide-wheel caps individually adjustable (patent pending).

Three vertical angle adjustment of the disk (used to suit different soil conditions).



SPECIFICATIONS	ADB1-328H2	ADB1-48H2	
Hitch type		3-point cat. II	
Number of discs	3	4	
Dimension of discs	in	28" x 1/4"	
Reversion		Hydraulic	
Width of cut	in	30"	40"
Width of gauge	in	58"	70"
Transport width	in	49"	57"
Depth of cut	in	16"	
Horizontal angle of discs	°	38 & 42	
Vertical angle of discs	°	15, 20 & 25	
Total length	in	88	110
Total height	in	44"	
Guide wheel		Adjustable	
Vertical tilt adjustment		Side independent	
Steering angle adjustment	°	3 positions (-10°, 0° y 10°)	
Arm length adjustment	in	4 lengths 6", 6" 7/8", 7" 3/4", 8" 5/8"	
Depth adjustment		Continuous	
Recommended power	hp	65-80	80-10

* Tecnomec Agrícola, S.A. de C.V. reserves the right to make any changes deemed necessary to the specifications without prior notice.

* Some pictures may include options that are not a part of the standard equipment.

Contact your BISON dealer for more info and other available options.

www.bison.com.mx



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905
Jesús María, Aguascalientes, México
Tel. (449) 92-BISON / Fax. (449) 922 4767