



REAR BLADE



-

T/LT Series blades are designed for tractors up to 55 hp. Choose between 4 to 8 feet wide moldboards.

NVHF Series blades are the ideal choice for up to 45 hp tractors. Choose between a 5 or 6 feet wide moldboard depending on your needs.



Ideal for light road maintenance, lawn care, gardening, and other light duty landscaping applications.

Offset, angle anf tilt options come standard on all models.



End plates allow rear blade to hold in material for filling.

Skid shoes increase the life of the cutting edge and avoid damaging the working surface while cleaning corrals or plowing snow.

Blades can be used year-around for leveling ground, roadside clearing and snow removal.

SPECIFICATIONS		NVHF-152	NVHF-182	NVHF-212			
Moldboard width	ft	5'	6'	7'			
Approximate weight	lb	250	280	310			
King pin diameter	in		2 5/8"				
Moldboard height & thickness	in		12 1/2 " x 1/4"				
Cuting edge			1/2" x 6" high carbon-steel blade, reversible, interchangeable				
Maximum tractor hp	hp		55 (2WD) & 50 (4WD)				
Hitch		3 - poin	3 - point category I and I quick hitch ¹				
Swing angle		20°,	20°, 40° and 60°, left or right.				
		3 forv	3 forward and 3 reverse positions				
Offset adjustment	in		0° to 12° left or right				
Tilt adjustment	0		0° to 20° left or right				
Total swing angle			360				
Parking stand	1		Standard				

SPECIFICATIONS		NVH-150-T	NVH-180-T	NVH-210-T	NVH-240-T	
Moldboard width	ft	5'	6'	7'	8'	
Approximate weight	lb	375	404 (372)	433	462	
King pin diameter		2 5/8"				
Moldboard height & thickness	in	17" x 1/4"				
Cuting edge	in	1/2" x 6" high carbon-steel blade (3/8" x 4" spring				
the second s		steel blade), reversible, interchangable				
Maximum tractor hp	hp	65 (2WD)				
Hitch		3 - point category I and I quick hitch ¹				
Swing angle		18°, 35° and 53° left or right				
		3 forward and 3 reverse positions				
Offset adjustment	in	6" or 12" left or right				
Tilt adjustment	0	7.5°, 15°, 22.5° and 30° up and down				
Total swing angle		360				
Parking stand		Standard				

	SPECIFICATIONS		NVHA-180	NVHA-210	NVHA-240		
	Moldboard width	ft	6'	8'	7'		
2	Approximate weight	lb	330	391	366		
z	Angle, tilt & offest	in	Manual or Hydraulically adjusted angle				
1			and manually tilt and offset				
	Moldboard height & thickness	in	15" height, 1/4" thickness				
	Cutting edge		1/2" x 6" reversible				
	Maximum tractor hp	hp	60 hp (4WD)				
	Hitch		3 Point CAT I				
	Total swing angle		360°				
	Offset adjustment	in	6" or 12" left or right				
	Tilt adjustment		0 to 20 degrees up or down				
				J			

* Tecnomec Agricola, S.A. de C.V. reserves the right to make any changes deemed necessary to the specifications without prior notice. * Some pictures may include options that are not a part of the standard equipment.

Contact your BISON dealer for more info and other available options.

www.bison.com.mx



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905 Jesús María, Aguascalientes, México Tel. +52 (449) 92-BISON / Fax. +52 (449) 922 4767