Bush Hoge TOUGH

Rear Discharge Finishing Mowers

BUSH HOG® TOUGH FEATURES

TOUGH Fabricated 7 Gauge Deck

TOUGH Cat 3 Drivelines

TOUGH Commercial Grade Greaseable Spindles

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Kevlar Reinforced Belt

TOUGH Powder Coat Paint



MODELS	RDTH60	RDTH72	
Cutting Width	60 inches	72 inches	
Cutting Height (1/2 inch increments)	11/2 to 61/2 inches	11/2 to 61/2 inches	
Tractor HP Range	15 - 35 PTO	20 - 40 PTO	
Type Hitch	Category I	Category I	
Size Blade	1/4 x 2.5 x 21 inches	1/4 x 2.5 x 25 inches	
Number of Blades	3	3	
Blade Tip Speed	18,231 FPM	18,272 FPM	
Blade Overlap	11/2 inches	11/2 inches	
Blade Uplift	Parallel	Parallel	
Driveline Size	ASAE Category 3	ASAE Category 3	
Front Roller Size (optional)	3 x 5 inches	3 x 5 inches	
Discharge	Rear	Rear	
Deck Plate	7 gauge	7 gauge	
Tire Size (solid tire & pneumatic)	31/4 x 101/4 inches	31/4 x 101/4 inches	
Belt	"B" size Kevlar	"B" size Kevlar	
Gearbox	45 HP	45 HP	
Tractor PTO Speed	540 RPM	540 RPM	
Belt Adjustment	Spring Loaded Idler	Spring Loaded Idler	
Approximate Weight	536 lbs	588 lbs	
Options	Front Roller Kit, Wheel Roller Bearing Kit	Front Roller Kit, Wheel Roller Bearing Kit	

Warranty 1 year limited warranty with a 5 year gearbox limited warranty

FEATURES

• Wide discharge • Floating top link • High blade tip speeds • Available in major tractor colors